

Marlow

DATASHEET [®]

WORK POSITIONING LANYARDS

New for 2022, Marlow's Work Positioning Lanyards are CE certified to EN 354 and are compatible with most approved climbing devices. The colour-coded lengths are made from 11mm Marlow Static LSK rope.



APPLICATIONS: Work positioning

MATERIAL:

COVER: Nylon
CORE: Nylon

CONSTRUCTION:

COVER: 16 plait
CORE: Multiple twisted cores

TEST STANDARDS: UKCA/CE EN 354

PROPERTIES: High strength, low elongation, good abrasion resistance, high energy absorption

COLOURS: Orange, red, yellow or blue

LENGTHS: 2m, 3m, 4m, 5m

TERMINATIONS: Sewn eye each end or snap hook (5m blue only)

PERFORMANCE

LENGTH	TOTAL WEIGHT	AV. BREAK LOAD	MIN BREAK LOAD (EN354)	COLOURS
m	g	kN	kN	
2m	188	30.9	22	Orange
3m	261	30.9	22	Red
4m	335	30.9	22	Yellow
5m	409	30.9	22	Blue
5m	517	30.9	22	Blue with snap hook termination

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.



Certification Number 315

ISO 9001